



Shunts

Class 0,5 acc. to DIN EN 60 051
Dimensions acc. to DIN 43 703

Type:
Shunt



Types and variants

Rated current A up to		Voltage drop					
		60 mV	weight kg	100 mV	weight kg	150 mV	weight kg
10 (with isolation base)	X	0,13	X	0,13	X	0,15	
15 (with isolation base)	X	0,13	X	0,13	X	0,15	
25 (with isolation base)	X	0,13	X	0,13	X	0,15	
40	X	0,12	X	0,14	X	0,16	
60	X	0,13	X	0,14	X	0,16	
100	X	0,13	X	0,15	X	0,17	
150	X	0,13	X	0,15	X	0,23	
200	X	0,43	X	0,55	X	0,65	
250	X	0,43	X	0,57	X	0,68	
300	X	0,54	X	0,60	X	0,70	
400	X	0,81	X	0,90	X	1,00	
500	X	0,81	X	0,92	X	1,10	
600	X	0,81	X	0,95	X	1,20	
800	X	1,45	X	1,85	X	2,00	
1000	X	1,47	X	1,90	X	2,10	
1200	X	1,47	X	2,00	X	2,20	
1500	X	2,00	X	2,76	X	3,80	
2000	X	2,90	X	3,40	X	4,10	
2500	X	3,00	X	4,70	X	5,60	
3000	X	3,50	X	4,80	X	5,90	
4000	X	4,20	X	5,60	X	11,70	
5000	X	4,40	X	5,90	X	12,30	
6000	X	11,30	X	12,50	X	14,60	
7000	X	11,30	X	12,80	X	15,30	
8000	X	15,40	X	22,40	X	25,30	
10000	X	21,00	X	22,90	X	26,60	
12000	X	26,40		on request		on request	
15000	X	32,00		on request		on request	
20000	X	44,00		on request		on request	

Surcharge for insulation base above 25 A (up to 25 A principally on insulation base)		60 mV	100 mV	150 mV
A	40	X	X	X
	60	X	X	X
	100	X	X	X
	150	X	X	X
	200	X	X	X
	250	X	X	X
	300	X	X	X
	400	X	X	X
	500	X	X	X