



Tube unit current transformer

for round conductors up to 21 mm

RSWR 21

Primary current 40 - 500 A



Type RSWR 21

Width	44 mm
Depth	30 mm
Busbar size	--
Round cond.	Ø 21 mm

Accessories incl. Foot fastening brackets
secondary terminal cover

Weight approx. 200 g
also possible in class 0,2; 0,2S und 0,5S



Types and variants

Primary current in A	VA	class 1		class 0,5	
		sec. 5 A	sec. 1 A	sec. 5 A	sec. 1 A
40	1	X*	X*	-	-
50	1	X	X	-	-
60	1,25	X	X	-	-
75	1,25	X	-	-	-
	2,5	X	X	-	-
80	2,5	X	X	-	-
100	1	-	-	X	X
	1,5	-	-	X	-
	2,5	X	X	-	-
125	1	-	-	X	X
	2,5	X	X	-	X
	3,75	X	X	-	-
150	2,5	X	X	X	X
	5	X	X	-	-
200	2,5	X	X	X	X
	5	X	X	X	X
	7,5	X	-	-	-
250	2,5	X	X	X	X
	5	X	X	X	X
	7,5	X	X	X	X
300	2,5	X	X	X	X
	5	X	X	X	X
	10	X	-	-	-
400	2,5	X	X	X	X
	5	X	X	X	X
	7,5	X	X	X	X
500	2,5	X	-	X	-
	5	X	-	X	-
	10	X	-	X	-

* Class 3 only!!!

Accessories: see accessories

