



Tube unit current transformer

for round conductors up to 28 mm

RSWR 28

Primary current 60 - 600 A



Type RSWR 28

Width	60 mm
Depth	35 mm
Busbar size	30 x 10 mm
Round cond.	Ø 28 mm

Accessories incl. Foot fastening brackets
secondary terminal cover

Weight approx. 300 g



Types and variants

Primary current in A	VA	class 1		class 0,5	
		sec. 5 A	sec. 1 A	sec. 5 A	sec. 1 A
60	1,25	X	X	-	-
75	1,25	X	X	-	-
80	1,25	X	X	-	-
100	1,25	X	X	X	X
125	2,5	X	X	-	-
	1,25	-	-	X	X
	2,5	X	X	-	-
150	3,75	X	X	-	-
	2,5	X	X	X	X
	5	X	X	-	-
200	2,5	X	X	X	X
	5	X	X	X	X
	7,5	X	X	-	-
250	2,5	X	X	X	X
	5	X	X	X	X
	7,5	-	-	X	X
	10	X	X	-	-
300	2,5	X	X	X	X
	5	X	X	X	X
	10	X	X	X	X
400	2,5	X	X	X	X
	5	X	X	X	X
	10	X	X	X	X
500	5	X	X	X	X
	10	X	X	X	X
	15	X	X	X	X
600	5	X	X	X	X
	10	X	X	X	X
	15	X	X	X	X

Accessories: see accessories

