



# Plug-in current transformers

for busbars 3 x 100 x 12 mm

## SWR 10056

Primary current 400 - 4000 A



### Type SWR 10056

<b>Width</b>	129 mm
<b>Depth</b>	30 mm
<b>Busbar size</b>	3x100x12 mm
<b>Round cond.</b>	Ø 56 mm

**Accessories incl.** busbar fixing material  
secondary terminal cover

**Weight** approx. 600 g  
also possible in class 0,2; 0,2S und 0,5S



### Types and variants

Primary current in A	VA	class 1		class 0,5	
		sec. 5 A	sec. 1 A	sec. 5 A	sec. 1 A
400	2,5	X	X	-	-
	5	X	X	-	-
500	2,5	X	X	-	-
	5	X	X	-	-
600	5	X	X	X	X
	10	X	X	-	-
750	5	X	X	X	X
	10	X	X	X	X
800	5	X	X	X	X
	10	X	X	X	X
1000	5	X	X	X	X
	10	X	X	X	X
	15	X	X	X	X
1200	5	X	X	X	X
	10	X	X	X	X
	15	X	X	X	X
1250	5	X	X	X	X
	10	X	X	X	X
	15	X	X	X	X
1500	5	X	X	X	X
	10	X	X	X	X
	15	X	X	X	X
1600	5	X	X	X	X
	10	X	X	X	X
	15	X	X	X	X
2000	5	X	X	X	X
	10	X	X	X	X
	15	X	X	X	X
2500	5	X	X	X	X
	10	X	X	X	X
	15	X	X	X	X
3000*	5	X	-	X	X
	10	X	X	X	X
	15	X	X	X	X
4000*	5	X	-	X	-
	10	X	-	X	-
	15	X	-	X	-

\*  $I_{cth} = 1,0 \times I_{pr}$

**Accessories:** see accessories

