



Plug-in current transformers

for busbars 4 x 120 x 10 mm

SWR 12070

Primary current 400 - 6000 A



Type SWR 12070

Width	159 mm
Depth	30 mm
Busbar size	4x120x10 mm
Round cond.	Ø 72 mm

Accessories incl.	busbar fixing material secondary terminal cover
--------------------------	--

Weight	approx. 950 g
	also possible in class 0,2; 0,25 und 0,5S



Types and variants

Primary current in A	VA	class 1		class 0,5	
		sec. 5 A	sec. 1 A	sec. 5 A	sec. 1 A
400	2,5	X	X	-	-
	5	X	X	-	-
500	2,5	X	X	-	-
	5	X	X	-	-
600	2,5	-	-	X	X
	5	X	X	X	X
	10	X	X	-	-
750	5	X	X	X	X
	10	X	X	-	-
800	5	X	X	X	X
	10	X	X	-	-
1000	5	X	X	X	X
	10	X	X	X	X
	15	X	X	-	-
1250	5	X	X	X	X
	10	X	X	X	X
	15	X	X	-	-
1500	5	X	X	X	X
	10	X	X	X	X
	15	X	X	-	-
1600	5	X	X	X	X
	10	X	X	X	X
	15	X	X	-	-
2000	5	X	X	X	X
	10	X	X	X	X
	15	X	X	X	X
2500	10	X	X	X	X
	15	X	X	X	X
	30	X	X	-	-
3000	10	X	X	X	X
	15	X	X	X	X
	30	X	X	-	-
4000	10	X	X	X	X
	15	X	X	X	X
	30	X	X	-	-
5000*	10	X	-	X	-
	30	X	-	X	-
6000*	10	X	-	X	-
	30	X	-	X	-

Accessories: see accessories

