



# Plug-in current transformers

for busbars 2 x 80 x 10 mm

## SWR 8030

Primary current 400 - 2500 A

### Type SWR 8030

<b>Width</b>	105 mm
<b>Depth</b>	30 mm
<b>Busbar size</b>	2x80x10 / 60x60 mm
<b>Round cond.</b>	Ø 70 mm

<b>Accessories incl.</b>	busbar fixing material secondary terminal cover
--------------------------	--

<b>Weight</b>	approx. 400 g
	also possible in class 0,2; 0,2S und 0,5S



### Types and variants

Primary current in A	VA	class 1		class 0,5	
		sec. 5 A	sec. 1 A	sec. 5 A	sec. 1 A
400	2,5	X	-	X	-
	5	X	-	X	-
500	2,5	X	X	X	X
	5	X	-	X	-
600	2,5	X	X	X	X
	5	X	X	X	X
750	2,5	X	X	X	X
	5	X	X	X	X
	10	X	-	-	-
800	2,5	X	X	X	X
	5	X	X	X	X
	10	X	-	X	-
1000	2,5	X	X	X	X
	5	X	X	X	X
	10	X	X	X	X
1250	2,5	X	X	X	X
	5	X	X	X	X
	10	X	X	X	X
1500	2,5	X	X	X	X
	5	X	X	X	X
	10	X	X	X	X
1600	2,5	X	X	X	X
	5	X	X	X	X
	10	X	X	X	X
2000	5	X	-	X	-
	10	X	-	X	-
	15	X	-	X	-
2500 *	10	X	-	X	-
	15	X	-	X	-

\*  $I_{cth} = 1,0 \times I_{pr}$

**Accessories:** see accessories

