



Plug-in current transformers

for busbars 30 x 10 (15) mm

SWR-L 3010

Primary current 60 - 600 A



Type SWR-L 3010

Width	70 mm
Depth	35 mm
Busbar size	30 x 10 mm
Round cond.	Ø 23 mm

Accessories incl. foot fastening brackets
busbar fixing material
secondary terminal cover

Weight approx. 400 g
also possible in class 0,2; 0,2S und 0,5S



Types and variants

Primary current in A	VA	class 1		class 0,5	
		sec. 5 A	sec. 1 A	sec. 5 A	sec. 1 A
60	1,25	X	X	-	-
75	2,5	X	X	-	-
80	2,5	X	X	-	-
100	1,25	-	-	X	-
	3,75	X	X	-	-
125	2,5	-	-	X	X
	5	X	X	-	-
150	2,5	-	-	X	X
	3,75	-	-	X	X
	5	X	X	-	-
	10	X	X	-	-
200	5	-	-	X	X
	7,5	-	-	X	X
	10	X	X	-	-
	15	X	X	-	-
250	5	-	-	X	X
	10	X	X	X	X
	15	X	X	-	-
300	10	X	X	X	X
	15	X	X	X	X
400	15	X	X	X	X
500	15	X	X	X	X
	20	X	X	X	X
600	15	X	X	X	X
	20	X	X	X	X
	25	X	X	X	X

Accessories: see accessories

