



# Split-core current transformers

for round conductors up to 18,5 mm

## SWUR 18

Primary current 50 - 250 A



### Type SWUR 18

<b>With</b>	44,4 mm
<b>Depth</b>	44,6 mm
<b>Busbar size</b>	--
<b>Round cond.</b>	Ø 18,5 mm

<b>Accessories incl.</b>	foot fastening brackets click-off hinge connection cable length = 1,5 m 2x0,75 mm <sup>2</sup> at 1 A sec. 2x2,5 mm <sup>2</sup> at 5 A sec.
--------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------

<b>Weight</b>	approx. 150 g
---------------	---------------



### Types and variants

Primary current in A	VA	class 3		class 1	
		sec. 5 A	sec. 1 A	sec. 5 A	sec. 1 A
50	1	-	X	-	-
60	0,6	X	-	-	-
	1,25	-	X	-	-
63	0,6	X	-	-	-
	1,25	-	X	-	-
75	0,6	X	-	-	-
	1,25	-	X	-	-
80	0,6	X	-	-	-
	1,25	-	X	-	-
100	0,2	-	-	X	X
	0,6	X	-	-	-
	1,5	-	X	-	-
125	0,2	-	-	X	-
	0,4	-	-	-	X
	0,6	X	-	-	-
	1,5	-	X	-	-
150	0,4	-	-	X	-
	0,6	X	-	-	X
	2	-	X	-	-
200	0,6	-	-	X	-
	1,25	-	-	-	X
	1,5	X	-	-	-
	2,5	-	X	-	-
250	0,6	-	-	X	-
	2,5	X	-	-	X
	3,75	-	X	-	-

