

from 01.03.2022
plus. 6,8 %
surcharge

Snap-on mounting base

for mounting on top hat rail 35 mm (DIN EN 60715)



€

Price

| Version | for CT type | net € |
|---------|-------------------------------|-------|
| A | SW 2010, SW-S 3010, SW-S 4010 | 1,50 |
| B | SW 3010 | 1,50 |
| C | SW-L 3010, SW-L 4010, WSWK-N | 1,50 |
| D | SW-S 2010, SW 4010, WSWK | 1,50 |
| E | RSW 14, RSW 21 | 1,50 |
| L | ASRD 205.37, ASRD 310.37 | 1,50 |

Sealed shutters

for sealing the secondary terminals after connection



€

Price

| Version | for CT type | net € |
|---------|---|-------|
| A | SW 2010, SW-S 3010, SW-S 4010, SW 20010, SW 12330 | 1,80 |
| B | SW-S 2010, SW 3010, SW-L 3010, SW 4010, SW-L 4010, WSWK, WSWK-N, WSW, SSW | 1,80 |
| C | SW-S 5010, SW 5010, SW 6010, SW 6030, SW 8010, SW 10010, SW 10055, SW 12838 | 1,80 |
| G | CSW 31, CSW 41 | 1,80 |
| H | CSW 51 | 1,80 |
| J | CSW 61, CSW 81, CSW 101 | 1,80 |

Quick fix fastenings

for mounting CT type CSW on the busbars



€

Price

| Version | Application | net € |
|---------|--|-------|
| A | Standard for 85°C continuous temperature | 2,00 |
| B | Heat stabilized for up to 130°C | 2,00 |