



Moving-iron measuring instruments

for alternating current and alternating voltage

Type:
WAS 45

from 01.03.2022
plus 6,8 %
surcharge

Snap-on fastening on top hat rail, 40-100 Hz, class 1,5
Please explicitly specify direct current!
Ammeters with 2-fold overload scale
Energy consumption: ammeters 0,6-1,5 VA, voltmeters approx. 2,5 VA

Type	WAS 45	
Installation width (mm)	45	(2.5 module width)
Scale length (mm)	43	
Weight (kg)	0,10	



Price

Measuring ranges		€
V	100	52,60
	250	
	500	
A	1	44,90
	1,5	
	2,5	
	4	
	6	
	10	
	15	
	25	50,00
for use with current transformer		
	sec. 5 A (0,6 VA)	42,20
	sec. 1 A (0,6 VA)	



Voltmeter selector switch

Type:
SUAS 45/7

from 01.03.2022
plus 6,8 %
surcharge

Snap-on fastening on top hat rail
for switchover between three different voltages and three phases against neutral acc. to VDE 0660

Type	SUAS 45/7
Operating voltage	max. 690 V
Operating current	max. 16 A
IP code	IP 54
Screw terminal	max. 4 mm
Installation width	52,5 mm (3 module widths)
Installation depth	45 mm
Price	€ 31,00

